

snapXP

Selfie Stand

SETUP GUIDE



Assembly Instructions

1

Unpack parts



Unpack the top tube, bottom tube and baseplate carefully placing parts on the floor.

Remove the hardware bag (black velvet pouch) from the case.

Flip bottom tube upside down and place baseplate on top.

2

Attach baseplate



To properly orient the baseplate align the green dots on tube bottom and baseplate top.

Install and tighten 4 bolts snugly using T-handle tool.

Tighten bolts snug being careful to not over tighten them.

3

Flip lower assembly



Pull the power cord from the bottom of the tube aligning it to the cord channel in the baseplate (the long slot).

Flip the assembly over so that the baseplate is now on the ground.

4

Connect power cables between tubes



Ensure that all power cords and blocks are securely installed in the power strips within the lower tube.

Pull out the three power cords.

(step 4 continued next page)



Connect the two black power cords to the power blocks in the top tube.

Connect the USB-C cord to the white power block in the lower tube.

5

Install the top tube



Place the top tube onto the bottom tube aligning green dots. Verify all cords are inside and not pinched.

Ensure top tube is sitting flush and four bolt holes are aligned.

6

Install four tube bolts



Install and tighten four bolts to secure top tube to bottom tube.

Tighten bolts snug being careful to not over tighten them.

7

Attach head assembly



Feed the wiring pigtail through the oval opening in the top of the pivoter.

(step 7 continued next page)



Attach the head assembly using the two front guide pins to line up the bolt holes.

8

Fasten head assembly



Install and tighten two bolts at the rear of the head assembly base to secure it to the pivoter.

Tighten bolts snug being careful to not over tighten them.

9

Connect power cords



Push the head assembly forward to maximum forward angle to access the head pigtail and pivoter pigtail.

Connect power cords for light and iPad.

10

Power unit



Plug the extension cord into a standard 120 VAC outlet.

Next turn on ring light power by turning rear switch clockwise.

Ideal light setting is usually between 1/4 and 1/2 power depending on the amount of ambient light in the area.

Instructions for securely packing the snapXP Selfie Stand

1

Make sure case is on a level surface.



2

Place head assembly in bottom of case



3

Place square foam pad on top of diffuser.



4

Place base plate in next.



5

Place square foam pad on top of base plate.



6

Place bottom tower piece in next.



7

Place rectangle foam pad separator next to tower piece.



8

Place top tower piece in next.





BEN LOCHARD

515.339.4783
hello@snapxp.com

www.snapXP.com